

# SAFETY DATA SHEET

## Rapallo Resins Aps

### A-Pox 900



## Material Safety Data Sheet

Page 1/5

---

Resin component A	A-Pox 900	Date: 13.12.2016
		Revision: 01

---

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Product name: A-Pox 900  
PR-no.:  
Product type: EPOXY RESIN  
Supplier: Rapallo Resins Aps  
Karetmagervej 19C  
DK 7100 Vejle

Contact numbers / Emergency: Tel. +45 82 12 12 12

---

### 2. HAZARDS IDENTIFICATION

2.1 Classification of mixture according to CLP GHS Regulation.

Eye Damage Category 1	H 318
Skin Corrosive Category 1C	H 314
Skin Sens. Category 1B	H 317
Aquatic Chronic Category 2	H 411
Reprotoxicant Category 1B	H 360F



### DANGER

Causes serious Eye damage. Causes skin burns. May cause an allergic skin reaction. May damage fertility. Toxic to aquatic life with long lasting effects.

---

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

Name of substance	CAS No:	EINECS	Weight%:	Signal word	H-sentences:
Bisphenol-A-diglycidylether reaktionsprodukt, mol wt <700	25068-38-6	500-033-5	30 - 60	Warning	319, 315, 317, 411
Bisphenol-F-epichlorhydrin epoxy	28064-14-4	-	20 - 30	Warning	319, 315, 317, 411
1,6-Hexandioldiglycidylether	16096-31-4	240-260-4	5-15	Warning	319, 315, 317, 411
Trimethylolpropantriglycidylether	30499-70-8	222-384-0	5-15	Danger	314, 318, 317, 411, 360F

# SAFETY DATA SHEET

## Rapallo Resins Aps

### A-Pox 900



Page 2/5

---

#### 4. FIRST AID MEASURES

Symptoms and effects:	Irritation of the skin and eyes.
First Aid - Inhalation:	No specific measures
First Aid - Skin:	Do not delay. Remove contaminated clothing. Wash skin with water using soap if available. If persistent irritation occurs, obtain medical attention.
First Aid - Eye:	Do not delay. Flush eye with water. If persistent irritation occurs, obtain medical attention immediately.
First Aid - Ingestion:	Do not induce vomiting. In the unlikely event of ingestion, obtain medical attention immediately.
Advice to Physicians:	If skin sensitisation has developed and a causal relationship has been confirmed, further exposure should not be allowed.

---

#### 5. FIRE FIGHTING MEASURES

Special hazards:	Not classified as flammable, but will burn. Carbon monoxide may be involved incomplete combustion occurs.
Extinguishing media- small fires:	Dry chemical powder, carbon dioxide foam, water spray or fog, sand or earth.
Large fires:	Foam, water spray or fog.
Unsuitable extinguishing media:	Water in a jet.
Protective equipment:	Full protective clothing and self-contained breathing apparatus.
Other information	Keep adjacent containers cool by spraying with water.

---

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Avoid contact with skin, eyes and clothing
Personal protection:	Wear protective clothing specified for normal operations ( see section 8).
Environmental precautions:	Prevent contamination of soil and water. Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. If materials enters drains it should be pumped out into a open vessel. emergence services may need to be called to assist in this operation.
Clean-up methods- small spillage:	Absorb or contain liquid with sand, earth or spill control material. Shovel material to labelled sealable container for safe disposal.
Large spillage:	Transfer to a labelled container for product recovery or safe disposal. Otherwise treat as for small spillage.

---

#### 7. HANDLING AND STORAGE

Handling:	Avoid contact with skin, eyes and clothing
Storage:	Keep container tightly closed and dry. Palletised loads should be stacked to a maximum of 4 high.
Storage temperatures:	Ambient.

---

#### 8. EXPOSURE CONTROLS/ personal protection

Occupational exposure standards:	None established.
Respiratory protection:	Not normally required. In a confined space wear half mask respirator with organic vapour cartridge and build-in particular filter NPF 20 ( gas only). If product is applied by spraying wear self contained breathing apparatus.
Hand protection:	Nitrile rubber gloves or butyl rubber gloves, gauntlet type.
Eye protection:	Mono goggles.
Body protection:	Standard issue work clothes, safety boots.

---

Page 3/5

# SAFETY DATA SHEET

## Rapollo Resins Aps

### A-Pox 900



#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Colour:	Clear / Pale yellow
Odour:	Slight
Density:	1000 - 1200 kg/m <sup>3</sup> @ 25 °C ( typical)
Dynamic viscosity:	0.8-1.2 Pa.s @ 25 °C
Boiling point:	Over 200 °C
Flash point:	>200 °C
Solubility in water	Negligible
Organic solvents:	0.0 %

---

#### 10. STABILITY/REACTIVITY

Stability:	Stable under normal use conditions. Reacts with strong oxidising agents. Polymerises exothermically with amines, mercaptans and Lewis acids at ambient temperature and above. Polymerises in contact with bases (e.g. caustic soda), ammonia, primary and secondary amines, alcohol's and acids.
Conditions to avoid:	Caustic soda can induce a vaporous polymerisation at temperatures over 150 °C.
Materials to avoid:	Strong oxidising agents. Caustic soda.
Hazardous decomposition products:	Hazardous decomposition products are not expected to form during normal storage.

---

#### 11. TOXICOLOGICAL INFORMATION

<b>Acute toxicity</b>	: Reprotoxicant Cat.1B, H360F: May damage fertility
Trimethylolpropantriglycidylether	
LD50 oral rat	300 mg/kg BW/Day, Reprotoxicant Cat.1B, H360F: May damage fertility
Eye irritation:	Irritant.
Skin irritation:	Irritant.
Respiratory irritation:	Not irritating.
Skin sensitisation:	Skin sensitizer.
Carcinogenicity:	A recent review of the available data by the International Agency for Research on Cancer (IARC), has concluded that DGE BPA is not classifiable as to its carcinogenicity.
Mutagenicity:	Positive in vitro, but negative in vivo assays.

---

#### 12. ECOLOGICAL INFORMATION

Basis for assessment:	Information given based on data on the components and the ecotoxicology of similar products.
Mobility:	Sinks in water.
Persistence/degradability:	Not readily biodegradable.
Bioaccumulation:	Has the potential to bio accumulate
Acute toxicity - fish:	Toxic, $1 < LC50 \leq 10$ mg/l.
Sewage treatment:	Toxic, EC50 > 1 - 10 mg/l, to organisms in sewage treatments plants. Toxic to aquatic organisms
EC50/48hours:	Daphnie 2.8 mg/l
EC50/96hours	Algae 220 mg/l
LC50/96 hours	Carp 3.6 mg/l

---

#### 13. DISPOSAL CONSIDERATIONS

Precautions:	See section 8. Refer to section 7 before handling the product or containers.
--------------	--

# SAFETY DATA SHEET

## Rapallo Resins Aps

### A-Pox 900




Waste disposal: Recover or recycle if possible. Otherwise incineration or dispose to licensed contractor.  
Product disposal: Drain container thoroughly. Rinse three times with suitable solvent. Treat rinses as for product disposal. After Draining, vent in a safe place away from sparks and re. Send to drum recovered or metal reclaimed.

Local legislation: Control of Pollution Act 1974.  
Control of Pollution ( Special waste) Regulations 1980.  
Environmental Protection Act 1990.

---

#### 14. TRANSPORT INFORMATION


##### Land transport ADR/RID



**ADR/RID class:** 9 miscellaneous dangerous substances and articles.

- **Danger code (Kemler):** 90
- **UN-Number:** 3082
- **Packaging group:** III
- **Hazard label** 9
- **Special marking:** Symbol (fish and tree)
- **Description of goods:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide resin)


##### Maritime transport IMDG:



**IMDG Class:** 9

- **UN Number:** 3082
- **Label** 9
- **Packaging group:** III
- **Marine pollutant:** Yes
- **Symbol** (fish and tree)
- **Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide resin)

##### Air transport ICAO-TI and IATA-DGR:



**ICAO/IATA Class:** 9

- **UN/ID Number:** 3082
- **Label** 9
- **Special marking:** Symbol (fish and tree)
- **Packaging group:** III
- **Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxide resin)

#### 15. REGULATORY INFORMATION

According to the CLP GHS regulation the product is labelled as follows:

# SAFETY DATA SHEET

## Rapallo Resins Aps

### A-Pox 900



#### DANGER

Contains:	Epoxy resin (Number average, Molecular weight < 700 ) and Trimethylolpropantriglycidylether.
H - phrases:	H 302: Harmful if swallowed H 312: Harmful in contact with skin H 332: Harmful if inhaled H 314: Cause severe skin burns and Eye damage. H 318: Causes serious eye damage. H 315: Causes skin irritation. H 317: May cause an allergic skin reaction. H 411: Toxic to aquatic life with long lasting effects. H360F: May damage fertility
P - phrases:	P 262: Do not get in eyes, on skin, or on clothing. P 273: Avoid release to the environment. P 280: Wear protective gloves/protective clothing/eye protection/face protection. P 302+P 352: <b>IF ON SKIN:</b> Wash with plenty of soap and water. P 305+P 351+P 338: <b>IF IN EYES:</b> Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P 337+P 313: If eye irritation persists: Get medical advice/attention.

#### 16. OTHER INFORMATION

EINECS :	All components listed.
MITI (Japan):	All components listed.
TSCA (USA):	All components listed.
AICS (Australia):	All components listed.
DSL (Canada):	All components listed.
Uses and restrictions:	- Compositions for the building and civil engineering industries e.g. flooring compounds, primers, adhesives, mortars, joints and grouts - Offshore & Marine applications
MSDS distribution:	This document contains important information to ensure the safe storage, handling and use of this product. The information in this document should be brought to the attention of the person in your organisation responsible for advising on safety matters.
Other information:	A-Pox is a trade mark from Rapallo Resins

---

DISCLAIMER: This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as a guarantee of any specific property of the product.

---

**Rapallo Resins Aps**  
**Karetmagervej 19C**  
**DK – 7100 Vejle**  
**Phone: +45 2348 5679**